

Specifications

STANDARD CONSTRUCTION

- Bulkhead (non-ribbed) 14 ga. galvanized steel
- Compartment Bottoms 16 ga. galvanized steel
- Compartment Tops 14 ga. galvanized steel (one-piece integral with loadspace centers)
- Crossmember-front 7 ga. hot-rolled formed channels
- Crossmember-intermediate 12 ga. galvanized steel
- Crossmember-rear 7 ga. hot-rolled formed channels
- Doors 20 ga. galvanized steel double panel
- End panels-front 14 ga. galvanized steel
- End panels-rear 14 ga. galvanized steel
- Fender panels 16 ga. galvanized steel
- Floor 12 ga. embossed galvanized treadplate
- Intermediate panels 16 ga. galvanized steel
- Loadspace inside centers ... 14 ga. galvanized steel (one-piece integral with compartment tops)
- Longitudinals 10 ga. galvanized formed
- Shelving 14 ga. high-spangle galvanized (250# static load capacity)
- Tailgate 18 ga. galvanized (double panel, formed construction)
- A-40 galvanized construction. Two-sided zinc coated galvanized (.40 oz zinc coating per square foot of steel) provides maximum rust and corrosion resistance.
- Body sides are constructed using plated lock-bolt fasteners.
- Floor understructure rigidly welded for structural integrity and durability. Mounting points re-inforced w/U-channel gussets.
- Bumper (optional) 12 ga. galvanized steel



Shown with optional recessed lighted bumper

STANDARD FEATURES / EQUIPMENT

- **Construction** - Lock-bolt to provide unbeatable durability, eliminates rust-causing welding and grinding, and promotes corrosion-free, long-lasting product. Floor understructure rigidly welded for structural integrity and undercoated for superior rust protection.
- **Compartment Tops** – Smooth seamless surface to enhance appearance.
- **Cutouts** – Openings in intermediate panels between horizontal and adjacent vertical compartments provides extended storage between compartments.
- **Door Hinges** - Concealed, bolt-on style provides increased security and clean appearance
- **Door Latches** - Bolt-on rotary style with stainless steel paddle handles and stainless steel pans.
- **Lock Cylinders** are keyed alike with double-bitted keys and are power door lock ready for easy after-market installation.
- **Door Striker** - Adjustable, bolt-on.
- **Vertical Doors** - Spring-loaded door holders to hold doors in the fully open position and assist in closing.
- **Horizontal Doors** – Use vinyl coated aircraft quality cables for support in open position.
- **Automotive Style Door Seal** - STAHL-engineered clip-on to allow easy removal for painting, replacement and quicker installation. Door seals against a flat surface for extra protection against water leakage.
- **Drip Rail** - Concealed to provide extra protection against water leakage.
- **Fender Panels** - Bolt-on die-stamped with radius wheel opening.
- **Tailgate** – Two point slam-locking featuring anti-rack/rattle hardware.
- **Shelving** – Bolt-in material trays with dividers.
- **Powder Coat Finish** – Body exterior, compartment interiors, and cargo area surfaces are finished in a durable, corrosion resistant white powder coat.
- **Undercoating** - On bottom of floor and wheelwells.
- **STAHL** 's exclusive 5-year "No Rust, No Bust" warranty.

Continues on reverse side...

STANDARD SHELVING PACKAGE

COMPARTMENT	BODY LENGTH	COMPT. WIDTH	CURBSIDE COMPARTMENTATION	STREETSIDE COMPARTMENTATION
Front vertical	98" 110" 134"	29.75" 33.25" 33.25"	(2) adjustable trays with moveable dividers	(2) adjustable trays with moveable dividers
Second vertical	134"	24.00"	(2) adjustable trays with moveable dividers	(2) adjustable trays with moveable dividers
Horizontal	ALL	47.125"	(1) adjustable tray with moveable dividers	Open
Rear vertical	98" 110" 134"	21.00" 29.75" 29.75"	(1) adjustable tray with moveable dividers	(1) adjustable tray with moveable dividers

DIMENSIONAL SPECIFICATIONS

DESCRIPTION	98VVS	98VVSLT	98VVD	110VVS	110VVD	110VVD	134VVD	134VVD
Overall Body Length	98"	98"	98"	110"	110"	110"	134"	134"
Loadspace Floor Width	48.50"	48.50"	52.50"	48.50"	52.50"	48.50"	48.50"	52.50"
Overall Body Width	79.98"	79.98"	96.00"	79.98"	96.00"	92.00"	92.00"	96.00"
Cab-to-axle	56.00"	56.00"	56.00"	60.00"	60.00"	60.00"	84.00"	84.00"
Front Vertical Width	29.75"	29.75"	29.75"	33.25"	33.25"	33.25"	33.25"	33.25"
<i>Clear door opening</i>	25.25"	25.25"	25.25"	28.75"	28.75"	28.75"	28.75"	28.75"
Second Vertical Width	n/a	n/a	n/a	n/a	n/a	n/a	24.00"	24.00"
<i>Clear door opening</i>	n/a	n/a	n/a	n/a	n/a	n/a	19.50"	19.50"
Horizontal Width	47.31"							
<i>Clear door opening</i>	45.25"							
Rear Vertical Width	21.00"	21.00"	21.00"	29.75"	29.75"	29.75"	29.75"	29.75"
<i>Clear door opening</i>	16.50"	16.50"	16.50"	25.50"	25.50"	25.50"	25.50"	25.50"
Vertical Compartment Height	39.50"							
<i>Clear door opening</i>	36.25"							
Horizontal Compartment Height	18.00"	11.25" *	18.00"	18.00"	18.00"	18.00"	18.00"	18.00"
<i>Clear door opening</i>	15.00"	9.66" *	15.00"	15.00"	15.00"	15.00"	15.00"	15.00"
Side Compartment Depth (useable)	13.81"	13.81"	19.68"	13.81"	19.68"	19.68"	19.68"	19.68"
Floor-to-Compartment Top Height	25.50"	22.00"	25.50"	25.50"	25.50"	25.50"	25.50"	25.50"
Tailgate Height Above Floor	9.25"							
Tailgate Height Overall	11.37"							

* Note: Top Pak clear door openings are from the bottom of the Top Pak pan.

OPTIONAL EQUIPMENT

- Back Up Alarms
- Bar Lock Master Locking System
- Bumpers
- Crane Reinforcement (2,000-4,000#)
- Dome Lights
- Drawers
- Folding Steps & Grab Handles
- Fuel Fill (Alum.)
- Primer Paint
- High Roof
- Hitches
- Hooks
- Ladder Rack
- Light Kit – LED
- Louvers
- Low Sliding Roof
- Off-Road Mounting Kit
- Shelves
- Paint and Installation
- Pipe Carrier
- Power Door Locks
- Tank Compartment
- Tie-Down Ring
- Tire Carrier
- Top Pak (add-on)
- Trays
- Treadbrite Overlay

Due to constant product evaluations and improvements, specifications are subject to change without notice.

