

Specifications

STANDARD CONSTRUCTION

- Bulkhead 14 gauge galvaneal
- Bumper..... 12 gauge galvaneal
- Compartment Bottoms 16 gauge galvaneal
- Compartment Tops 14 gauge galvaneal
- Crossmember-front 7 gauge formed
- Crossmember-intermediate 12 gauge formed
- Crossmember-rear 7 gauge formed
- Doors..... 20 gauge galvaneal outer panel with 14 gauge galvaneal inner panel
- End panels-front..... 16 gauge galvaneal
- End panels-rear 16 gauge galvaneal with rivet-on thermo-plastic olefin end cap
- Fender panels 16 gauge galvaneal with rivet-on composite fender flare
- Floor 12 gauge treadplate
- Intermediate panels 16 gauge galvaneal
- Loadspace inside centers ... 14 gauge galvaneal (one piece with compartment tops)
- Longitudinals 11 gauge formed
- Shelving 16 gauge high-spangle galvanized (250# capacity)
- Tailgate 16 gauge galvaneal (double panel, formed construction)
- A-40 galvaneal construction. Two-sided zinc coated galvaneal (.40 oz zinc coating per square foot of steel) provides maximum rust and corrosion resistance.
- Body construction is welded with front end panels and rear end panels welded at the top. One-piece construction compartment tops and inside centers.
- Flush outside body surfaces with unexposed edges for rust resistance.



STANDARD FEATURES / EQUIPMENT

- **Includes** - Galvaneal bumper is recessed, features non-skid step and hitch plate, and houses clearance lights, ID lights, license plate and license plate light.
- **Body Mounting Kit** - Bodies have universal understructures.
- **Contoured Body Sides** - Complement the chassis styling.
- **Cutout** – Opening in intermediate panel between horizontal and rear vertical compartments provides extended storage between compartments.
- **Horizontal Door** - Vinyl coated aircraft cables on horizontal doors.
- **Doors** - Flush-mounted doors do not allow metal-to-metal contact when closed.
- **Door Hinges** - Concealed to complement chassis styling and add security.
- **Door Holders** - Double spring style on vertical doors to hold door in open and closed positions.
- **Door Latches** - Rotary style with stainless steel paddle handles and galvaneal steel pans. Latches are removable for ease of repair or replacement.
- **Door Seal** – STAHL-engineered clip-on to allow easy removal for painting, replacement and quicker installation. Door seals against a flat surface for extra protection against water leakage.
- **Drip Rail** - Runs the full length of the body and provides extra protection against water leakage.
- **Fuel Fill Door** - Automotive style door is located on streetside front for G101, streetside rear for single wheel G112 and streetside dual (front and rear) for G112 and G136.
- Lights include combination stop, tail and back up and complement the chassis styling.
- **Lock Cylinders** - Keyed alike with double-bitted keys.
- **Primer** - High grade automotive type. Bodies are cleaned with a high-temperature, high-pressure chemical solution prior to prime painting.
- **Striker** - Adjustable, bolt-on.
- **Tailgate** - Two point slam-locking style features locking rotary latch, anti-rack/rattle hardware, and vinyl coated cables to protect against paint damage.
- **STAHL**'s exclusive 5-year "No Rust, No Bust" warranty.

STANDARD SHELVING PACKAGE

COMPARTMENT	BODY SIZE	COMPT. WIDTH	CURBSIDE	STREETSIDE
Front vertical	101" 112" 136"	29 13/16" 33 13/16" 33 13/16"	One (1) adjustable material tray with adjustable dividers and one (1) adjustable shelf	One (1) adjustable material tray with adjustable dividers and one (1) adjustable shelf
Second vertical	136"	23 15/16"	One (1) adjustable material tray with adjustable dividers and one (1) adjustable shelf	One (1) adjustable material tray with adjustable dividers and one (1) adjustable shelf
Horizontal	ALL	46 3/16"	One (1) adjustable material tray with dividers	Open
Rear vertical	101" 112" 136"	20 15/16" 27 15/16" 27 15/16"	One (1) adjustable material tray with adjustable dividers and shuttle cutout from horizontal to rear vertical	One (1) adjustable material tray with adjustable dividers and shuttle cutout from horizontal to rear vertical

DIMENSIONAL SPECIFICATIONS

Standard Height Models

DESCRIPTION	G101	GD101	G112S	G112	G112	G136	G136
Body Length (inside bed)	101.5"	101.5"	112.5"	112.5"	112.5"	136.25"	136.25"
Body Length (overall)	103.5"	103.5"	114.25"	114.25"	114.25"	138.25"	138.25"
Loadspace Floor Width	48.5"	52.5"	48.5"	52.5"	48.5"	52.5"	48.5"
Overall Body Width	79.75"	95.75"	79.75"	95.75"	91.75"	95.75"	91.75"
Cab-to-axle	56"	56"	60"	60"	60"	84"	84"
First vertical width	29.81"	29.81"	33.81"	33.81"	33.81"	33.81"	33.81"
<i>Clear door opening</i>	23.5"	23.5"	27.5"	27.5"	27.5"	27.5"	27.5"
Second vertical width	n/a	n/a	n/a	n/a	n/a	23.93"	23.93"
<i>Clear door opening</i>	n/a	n/a	n/a	n/a	n/a	18.875"	18.875"
Horizontal width	46.18"						
<i>Clear door opening</i>	44"						
Rear vertical width	20.93"	20.93"	27.93"	27.93"	27.93"	27.93"	27.93"
<i>Clear door opening</i>	16.5"	16.5"	23.5"	23.5"	23.5"	23.5"	23.5"
Vertical compartment height	40"						
<i>Clear door opening</i>	33"						
Horizontal compartment height	19.18"						
<i>Clear door opening</i>	12.5"						
Compartment depth	15.75"	21.75"	15.75"	21.75"	21.75"	21.75"	21.75"
Floor-to-compartment top height	26"						
Tailgate height above floor	13.75"						

OPTIONAL EQUIPMENT

- Back Up Alarm
- Bar Lock
- Compartment Lights
- Crane Reinforcement
- Drawer Packages
- Hitches
- Hook
- Ladder Rack
- Light Kit
- Louver
- Low Sliding Roof
- Mounting Kit
- Off-Road Mounting Kit
- Paint and Installation
- Pipe Carrier
- Power Door Locks
- Rope Rail
- Shelves
- Tie-Down Ring
- Tire Carrier
- Trays



Due to constant product evaluations and improvements, specifications and options are subject to change without notice.