

Specifications

STANDARD CONSTRUCTION

- Crossmembers of steel floors are 5-5/8", 11 ga. high strength formed steel "C" channels (50,000 psi)
- Crossmembers of wood floors are 4", 11 ga. high strength formed steel "C" channels (50,000 psi)
- Endrails and siderails are 5-5/8" 12 ga. high-strength steel (50,000 psi)
- Flooring is 2" x 6" tongue-and-groove treated dense pine
- Smooth steel flooring is 10 ga. steel.
- Treadplate flooring is 12 ga. steel.

STANDARD FEATURES / EQUIPMENT

- **Crossmember spacing:**
Standard-duty platforms: 24" on all lengths.
Heavy-duty platforms: 18" on all lengths.
Commercial-duty platforms: 12" on all lengths.
- **Gussets:** Front and rear end gussets are standard.
Standard-duty platforms: every other crossmember.
Heavy-duty platforms: every other crossmember with crossmember 18" on center.
Commercial-duty platforms: every crossmember with crossmembers 12" on center.
- **Longsills:** Installed with 34" spacing.
Standard-duty platforms: 4" 10 ga. formed channel.
Heavy-duty and Commercial-duty platforms: 6" 8.2# structural steel on 12' and shorter
Commercial-duty platforms: 7" 9 .8# structural steel on 14' and longer
- **Recessed lights** with shock-resistant rubber grommets and loom-protected wires.
- 1.7" x 3.75" reinforced **stake pockets** on 24" centers.
- **Steel platforms** are finish painted black.
- **Wood platforms** are treated with black tinted wood protector.
- All platforms carry **STAHL**'s 3-year limited **warranty**.



STAKE RACKS

- Black finish paint on steel racks and hardware.
- 30" and 40" 14 ga. **galvanneal steel** stakes and roll-formed 16 ga. slats.
- Optional 40" southern yellow pine or apitong wood (stakes are galvanneal steel, slats are wood).
- Spring-loaded, anti-rattle, zinc-plated, heavy-duty hardware.

SOLID SIDES

- Black finish paint.
- Rectangular weld-on bulkhead is made from 10 gauge **galvanneal steel** with window cutout.
- 40" high 12 ga. rust-resistant **galvanneal steel sides** with integral reinforcement ribs.
- Sides are removable / bolt-on (standard) or weld-on (optional).
- Swing-out rear barn doors with heavy-duty three-point catch, spring latch door holders at bottom of rear doors.



Continues on reverse side...

BULKHEADS

- All bulkheads are finish painted black.
- All bulkheads have a styled, punched window pattern.
- Rectangular Drop-in: 38", 40", 48", or 56" high and 80", 90, or 96" wide; 12 ga. **galvanneal steel**.
- Tapered Drop-in: 38", 40", or 48" high and 90" or 96" wide; 12 ga. **galvanneal steel**.
- Rectangular Weld-on: 40", 48", or 56" high and 96" wide; 10 ga. **galvanneal steel**.

HOIST FEATURES

- 3800 PSI Operating pressure
- 5" cylinder with 20" stroke
- Internal relief valve
- 2 gallon reservoir

DIMENSIONAL SPECIFICATIONS

CROSSMEMBER SPACING

STAKE BODY Length	CAB-TO-AXLE	STANDARD DUTY			HEAVY DUTY			COMMERCIAL DUTY		
		Width 80"	Width 90"	Width 96"	Width 80"	Width 90"	Width 96"	Width 80"	Width 90"	Width 96"
8.5"	56"-60"	24"	24"	24"	18"	18"	18"	12"	12"	12"
9.5"	60"		24"			18"	18"		12"	12"
10.5"	60"-72"		24"			18"	18"		12"	12"
12.5"	84"-102"		24"			18"	18"		12"	12"
14.5"	102"-124"									12"
16.5"	114"-126"									12"
18.5"	120"-152"									12"
20.5"	136"-168"									12"
22.5"	144"-192"									12"
24.5"	165"-196"									12"

OPTIONAL EQUIPMENT

- Apitong Wood Floor
- Bulkhead
- Floor Overlays (smooth steel or treadplate)
- 40" High Solid Sides
- Tarp for Solid Sides
- Contractor sides
- **STAHL** hoist
- Tie down rails and rings
- "L" and "I" Cross-body toolboxes
- Underbody toolboxes
- Wood Stake Racks
- Swing out rear racks
- Mud flaps
- Special Finish Paint Colors
- ICC bumpers or towing bumpers
- Specially modified platforms available upon request

Due to constant product evaluations and improvements, specifications and options are subject to change without notice.

